










Hytech runs the line 'type 30' of the Ingersoll-Rand compressor range. The type 30's are two stage air compressors for pressures up to 16 bars (235 psi.) Standard features are:

Drive: V-belt. Provision is made for easy adjustment.

Belt guard provides operator protection at all times.

Aftercoolers is of finned tube type and mounted on top of the compressor.



	MOD								
		455568 77809901	L.	Pk/kW	L./min	rpm	bar	cm	kg.
23ANL	23ANLE20	42929190	200	2/1.5	140	730	6.9	205x75x130	260
235HNL	235HNL30	55890602	200	3/2.2	190	490	6.9	205x75x130	325
235HNL	235HNL40	55889059	300	4/3	270	710	6.9	205x75x130	335
5T2NL	5T2NLH100	55890628	500	10/7.5	740	900	8.6	210x90x165	435
10T3NL	10T3NLH150	55890636	500	15/11	1100	670	8.6	210x90x175	720
10T3NL	10T3NLH200	55889174	500	20/15	1450	890	8.6	210x90x175	720
23ANL	23ANLX20	55890537	-	2/1.5	140	730	6.9	125x80x85	120
235HNL	235HNLX30	55890545	-	3/2.2	190	490	6.9	125x80x85	170
235HNL	235HNLX40	55890552	-	4/3	270	710	6.9	125x80x85	180
5T2NL	5T2NLX55	55890560	-	5.5/4	460	600	8.6	155x85x110	170
5T2NL	5T2NLX100	42924225	-	10/7.5	740	900	8.6	155x85x110	490
10T3NL	10T3NLX150	55890586	-	15/11	1100	670	8.6	170x100x125	500
10T3NL	10T3NLX200	55890594	-	20/15	1450	890	8.6	170x100x125	520



Hyperbaric Technology B.V.

Blik 16 - 4941 SG - Raamsdonksveer - The Netherlands

☎ +31 (0)162 522202 ☎ +31 (0)162 519069

✉ hytech@hytech.nl 🌐 http://www.hytech.nl