

OFFSHORE OIL & GAS CONFIGURATION

PRO 4 OG 300XL



CONFIGURATION COMPONENTS

THE PRO 4 OG 300XL been specifically configured for Offshore Oil & Gas Operations to quickly and effectively perform a variety of advanced inspection and observation tasks. It is delivered with the main components – Submersible, Control Panel, and Tether and includes a LYYN Hawk Real Time Video Enhancement feature for lower visibility environments, a BlueView P900-130 Imaging Sonar for target location, and an integrated Smart Tether Positioning System. This system is also delivered standard with 315 m (1,030 ft) total of modular tether segments for **deep** dives, a tether management system, and a spare ROV submersible for redundancy.

Depth Rating: 305 m (1,000 ft)
Maximum Speed: 4.2 Knots



- Pro 4 ROV Submersible
- Pro 4 Professional ICB
- Integrated Toughbook Computer
- Rugged Hand Controller
- Fixed Second Camera
- BlueView P900-9130 Multibeam Sonar
- LYYN Video Enhancement Technology
- Smart Tether Positioning System
- Manipulator
- Plug and Play Modular Tether
 - 75m (250 ft) Neutral Buoyancy
 - 200m (650 ft) Negative Extension
 - 40m (130 ft) Neutral Buoyancy Performance
- Extended Tether Deployment System
- 5 Day Training - Service Agreement
- Spare ROV Submersible Only

www.videoray.com

580 Wall Street Phoenixville, PA 19460 USA
phone: +1 (610) 458-3000 fax: +1 (610) 458-3010 email: info@videoray.com

SPECIFICATIONS



SYSTEM

Total System Weight	47 kgs (105 lbs)
Cases	3 watertight, rugged cases
Owners Manual	Hard copy and digital
System Tool Kit	Basic tool kit and spares
Communications Protocol	RS485
Warranty	2 year limited

SUBMERSIBLE

Depth Rating	305m (1,000 feet)
Size	36.8, 29.2, 22.2 cm (14.5, 8.5, 9 in)
Weight	4.5 kgs (10.5 lbs)
Ballast	Tool-less ballast system with complete ballast set

Propulsion

Horizontal	4.2 knots 2 brushless Direct drive 100mm propellers	Vertical	1 brushless Geared 65mm propeller
------------	--	----------	---

Camera

Main	High resolution NTSC or PAL Color and B&W Wide Dynamic Range Digital slow shutter White balance 20+ Real time camera settings	Second	High resolution NTSC or PAL Color 3.6mm fixed lens Color .1 lux 90° horizontal/140° diagonal Fixed, adjusted manually
Sensitivity	Color mode: .004 lux B&W mode: .0001 lux	Sensitivity	Color .1 lux
View Angle	90° horizontal/140° diagonal	View Angle	90° horizontal/140° diagonal
Tilt	180° servo control	Tilt	Fixed, adjusted manually

Lighting

LED array with 24 emitters - Expandable
3,600 lumens (5,760 max)

Sensors

3D-tilt Compensated Compass	Leak Indicator
Accelerometer	Water temperature
MEMS Gyro	Internal temperature

CONTROL CONSOLE

Size	53, 43, 22 cm (21,17, 8.5 in)
Weight	16 kgs (35 lbs)
Computer	Toughbook MIL-STD-810/IP54 with 10.5 inch touch screen display
Main Display	15 inch (shared desktop with computer display)
Controller	12 Button Professional Joystick (also delivered with wireless Logitech Wingman controller)
Recording	Integrated Recording (.WMV, .MPG format) One button hand controller recording
Overlay	Date, Time, Depth, Heading, Customized Text, Logo
Video Out	Digital or analog composite

TETHER

315m (1,030 ft) **total length**, modular plug and play tether (Excluding 40 m Smart Tether)
75m Standard Neutral Buoyancy Tether - 10mm diameter, 454 kg (1,000 lbs) breaking strength
200m Extension Negative Buoyancy Tether - 8mm diameter, 454 kg (1,000 lbs) breaking strength
40m Professional Performance Tether - 8mm diameter, 454 kg (1,000 lbs) breaking strength

Management Extended Tether Deployment System

INTEGRATED ACCESSORIES

Manipulator	Single Axis
Sonar	BlueView P900-130 Multibeam Imaging Sonar
Positioning	Smart Tether Non-Acoustic Positioning System
Enhancement	Lynn Hawk Real Time Video Enhancement

TRAINING

5 Day Standard Training - 2 Seats

SERVICE

2 Year Service Agreement*
*Maximum 20 Hours